



Product Specifications
Stellar Select Hotmelt Tape



Document Issue Date: 01-July-2024

Nominal Values:	
Item ID#	160-E12147
Backing:	1.1MIL (Blown film)
Adhesive:	Synthetic Rubber / Resin
Color:	Clear
Total Thickness:	1.8 MIL
Adhesion to Steel:	14.978 N/in
Tensile Strength:	102.5 N/in
Elongation (% at break)	149.51%
Temperature Range:	+45°F to +120°F (Application) -10°F to +140°F (Operating)
Government Compliance:	Complies with the Federal Food, Drug and Cosmetic Act, CFR Title 21, Subpart B, Par. 175.105 (covers the use of pressure-sensitive adhesives and tapes for 'indirect contact' food packaging, such as box sealing). CID A-A-1684C.
(Tolerance +/- 10%); We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. Stellar Safety Supply WILL NOT BE LIABLE FOR DAMAGES IN EXCESS OF THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.	