



Product Specifications

Stellar Hotmelt Tape, 2 mil 48mm, Clear



Document Issue Date: 01-July-2024

Nominal Values:	
Item ID#	160-E12149
Backing	1.1MIL (Blown film)
Adhesive	Synthetic Rubber / Resin
Color	Clear
Total Thickness	2 MIL
Adhesion to Steel	18.71 N/in
Tensile Strength	132.526 Mpa/in
Elongation (% at break)	176.852%
Peel Adhesion	14.106 N/in
Temperature Range	+45°F to +120°F (Application) -10°F to +140°F (Operating)
Government Compliance	Complies with the Federal Food, Drug and Cosmetic Act, CFR Title 21, Subpart B, Par. 175.105 (covers the use of pressure-sensitive adhesives and tapes for 'indirect contact' food packaging, such as box sealing). CID A-A-1684C.

(Tolerance +/- 10%); We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. Stellar Safety Supply WILL NOT BE LIABLE FOR DAMAGES IN EXCESS OF THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.